

UDC 681.142.01

## DATA SINGLE-ERROR CORRECTION METHOD OF A RESIDUE CLASS CODE

Viktor Krasnobayev<sup>1</sup>, Sergey Koshman<sup>1</sup>, Maksym Silenko<sup>1</sup>, Sergey Moroz<sup>2</sup>

<sup>1</sup> V. N. Karazin Kharkiv National University, 4 Svobody Sq., Kharkiv, 61022, Ukraine  
[v.a.krasnobaev@gmail.com](mailto:v.a.krasnobaev@gmail.com), [s\\_koshman@ukr.net](mailto:s_koshman@ukr.net), [maximkasilenko@gmail.com](mailto:maximkasilenko@gmail.com)

<sup>2</sup> Kharkiv Petro Vasylenko National Technical University of Agriculture, 19 Rizdviana St., Kharkiv, 61052, Ukraine  
[frost9i@ukr.net](mailto:frost9i@ukr.net)

**Reviewer:** Serhii Toliupa, Doctor of Sciences (Engineering), Full Prof., Taras Shevchenko National University of Kiev, 81 Lomonosova St., Kyiv, 03189, Ukraine.  
[tolupa@i.ua](mailto:tolupa@i.ua)

Received on March 2018

**Abstract:** This article describes the method of correcting of single errors in the residue class (RC). The study of this method makes it possible to create effective systems for monitoring data errors of computer systems in RC. The results of the analysis of the corrective capabilities of the arithmetic code in the RC showed a high efficiency of using non-positional code structures, due to the presence in the non-positional code structure of primary and secondary redundancy. The paper shows that the corrective capabilities of codes in the RC depend on the introduction of additional redundancy in the code structure. At the same time, if certain conditions are met, the data can be corrected by introducing only one test base. The article provides examples of monitoring and correcting of single errors were represented by codes in the RC.

**Keywords:** non-positional code structure; residue classes; positional numeral systems; minimum code distance; error-control coding; data diagnosing and correction.

### 1 Introduction

In general, in order to verify, diagnose and correct errors a code structure requires a certain error-correcting capability. In this case, code is required to be introduced to data duplication, i.e. information redundancy should be implemented. All of the above fully refers to a non-positional code structure (NCS) in residue classes (RC) [1-3].

For each random RC the amount of redundancy  $R = M_0 / M$  uniquely determines correction capability of a non-positional error-correcting code. Error correcting codes in RC can have any given values of minimum code distance (MCD)  $d_{\min}^{(RC)}$ , which depends on the value of redundancy  $R$ . The acquainted theorem [1] establishes a link between error-correcting code redundancy  $R$ , the value of MCD  $d_{\min}^{(RC)}$ , and the amount of RC check bases  $k$ .

Error-correcting code has MCD values  $d_{\min}^{(RC)}$  in case when the degree of redundancy  $R$  is not less than the product  $d_{\min}^{(RC)} - 1$  of RC bases. On the one hand we get  $R \geq \prod_{i=1}^{d_{\min}^{(RC)}-1} m_{q_i}$ , but on the other

hand  $R = M_0 / M = \prod_{i=1}^{n+k} m_i / \prod_{i=1}^n m_i = \prod_{i=1}^k m_{n+i}$ . In this case, it's correct to state that  $d_{\min}^{(RC)} - 1 = k$ , or

$$d_{\min}^{(RC)} = k + 1. \quad (1)$$

There are two approaches to solve the problem of providing NCS with all required error-correcting properties in RC.

The first approach. If the requirements for error-correcting properties of NCS are known, for example, depending on amount of errors being detected  $t_{\text{det}}$  or corrected  $t_{\text{cor}}$ , required information redundancy  $R$  should be introduced, using the amount of  $k$  or the value  $\{m_{n+k}\}$  of check bases.

Redundancy  $R$  determines minimum code distance  $d_{\min}^{(RC)}$  of NCS in RC.

Then, according to the error-control coding (ECC) theory for an ordered ( $m_i < m_{i+1}$ ) RC we have that

$$t_{\text{det.}} \leq d_{\min}^{(RC)} - 1, \quad (2)$$

$$t_{\text{det.}} \leq k; \quad (3)$$

$$t_{\text{cor.}} \leq \left\lfloor \frac{d_{\min}^{(RC)} - 1}{2} \right\rfloor, \quad (4)$$

$$t_{\text{cor.}} \leq \left\lfloor \frac{k}{2} \right\rfloor. \quad (5)$$

The second approach. For a given NCS  $A_{RC} = (a_1 \| a_2 \| \dots \| a_{i-1} \| a_i \| a_{i+1} \| \dots \| a_n \| \dots \| a_{n+k})$  (for a given value  $k$ ) its error-correcting capabilities (determined by the  $d_{\min}^{(RC)}$  value) of RC code are defined by the expressions (3) and (5).

Note that, if an ordered RC is extended by adding  $k$  check bases to  $n$  information modules, then MCD  $d_{\min}^{(RC)}$  of the error-correcting code is increased by the value  $k$  (see expression (1)).

The values of  $d_{\min}^{(RC)}$  can be also increased by decreasing the number  $n$  of information bases, i.e. by transitioning to less accurate calculations. It's clear that in RC between error-correcting  $R$  properties of error-control codes and calculation accuracy  $W$  inverse proportion exists. The same computer can perform arithmetical calculations or any other math operations both with high  $W$  accuracy but a low error-correcting  $R$  capability and with lower  $W$  accuracy, but with a higher capability  $R$  of error detection and correction in order to verify, diagnose and correct data faults, as well as to demonstrate higher data processing performance (the time to execute basic operations is inversely proportional to  $n$  information bases in RC) [2,4,5].

## 2 The main part

Now we'll analyze the process of single-error correcting data capability in RC given the minimal information redundancy by introduction of a single ( $k = 1$ ) check base. In this case, according to the error control coding theory in RC [1, 2], MCD is equal to the value  $d_{\min}^{(RC)} = k + 1$ . If  $k = 1$ , then MCD is  $d_{\min}^{(RC)} = 2$ , which, as according to the general error control coding theory, ensures any single-error detection (an error in one of the residues  $a_i$  ( $i = \overline{1, n+1}$ )) in NCS.

In general, just as in the positional numeral system (PNS), the process of data error correction in RC consists of three stages. The first stage – data checking (correctness or incorrectness verification of the initial number  $A_{RC}$ ). On the second stage diagnosing the false  $\tilde{A}_{RC}$  number (detection of a single corrupted residue  $\tilde{a}_i$  of the number  $\tilde{A}_{RC}$  to the base  $m_i$  in RC). And, finally, on the third stage correcting the invalid residue  $\tilde{a}_i$  to its true value  $a_i$  of the number, i.e. correcting false  $\tilde{A}_{RC}$  number (getting the correct number  $A_{RC} = \tilde{A}_{\text{cor.}}$ ).

The degree of information redundancy  $R$  (code error-correcting property) is estimated by the value of MCD  $d_{\min}^{(PNS)}$ . As previously noted, the value of MCD is defined by the ratio  $d_{\min}^{(RC)} = k + 1$ , where  $k$  is the amount of check bases in an ordered RC.

Let's start with the NCS  $A_{RC} = (a_1 \| a_2 \| \dots \| a_{i-1} \| a_i \| a_{i+1} \| \dots \| a_n \| \dots \| a_{n+k})$  in RC having a minimal ( $k = 1$ ) additional information redundancy. In this situation it's considered that  $d_{\min}^{(RC)} = 2$ .

According to the error control coding theory in PNS if the minimum code distance is granted to be  $d_{\min}^{(PNS)} = 2$ , a single error in a code structure is ensured to be detected. In PNS a single error is

understood as a corruption of a single information bit, for instance  $0 \rightarrow 1$  or  $1 \rightarrow 0$ . In order to correct this single error it's required to ensure the condition, when  $d_{\min}^{(PNS)} = 3$ .

Contrary to PNS, a single error in RC is understood as a corruption of a single residue  $a_i$  modulo  $m_i$ . Inasmuch as the residue  $a_i$  of the number  $A_{RC} = (a_1 \| a_2 \| \dots \| a_{i-1} \| a_i \| a_{i+1} \| \dots \| a_n \| a_{n+1})$  modulo  $m_i$  contains  $z = \{\lceil \log_2(m_i - 1) \rceil + 1\}$  binary bits, then it's formally correct to be considered that if  $d_{\min}^{(RC)} = 2$  ( $k = 1$ ) is within limits of a single residue  $a_i$ , an error cluster can be detected in RC, with its length not exceeding  $z$  binary bits. However in RC, as it is shown in literature [1, 2, 5], there are some cases when a single errors can be corrected while  $d_{\min}^{(RC)} = 2$ .

In the light of specific features and properties of NCS representation in RC an error-correcting capability given  $d_{\min}^{(RC)} = 2$  can be explained in the following manner.

1. A single error in PNS and in RC are different concepts, as it was shown before. With that being said, MCD  $d_{\min}^{(PNS)}$  for PNS and  $d_{\min}^{(RC)}$  for RC has different meaning and measure.

2. Existing (implicitly) intrinsic (natural, primal) information redundancy in NCS, being stored in residues  $\{a_i\}$  due to their forming procedure, has a positive effect (from the perspective of increasing data jam-resistance, transfer and processing reliability) that kicks in only with the presence of a subsidiary (artificial, secondary) information redundancy. An artificial information redundancy in NCS is being introduced by using (additionally to  $n$  information bases)  $k$  check bases in RC. A distinguishing feature of RC is its significant display of the intrinsic information redundancy only if the subsidiary one is also present, due to introduction of check bases.

3. As shown in [1,2,5], error control code in RC with mutually prime bases has the MCD value of  $d_{\min}^{(RC)}$  only if the information redundancy level is not less than the product of any  $d_{\min}^{(RC)} - 1$  bases of a given RC.

The availability and interaction of primary and secondary redundancies during the subsidiary tests (time redundancy usage) of error-correcting process, which may provide a single-error error-correcting capability in RC, while  $d_{\min}^{(RC)} = 2$  (given  $k = 1$ ).

Indeed, according to the expressions (3) and (5) for an ordered RC following conclusions can be made: with a single ( $k = 1$ ) check base  $m_{n+1}$  in RC, the NCS  $A = (a_1 \| a_2 \| \dots \| a_{i-1} \| a_i \| a_{i+1} \| \dots \| a_n \| a_{n+1})$  can have several values of  $d_{\min}^{(RC)}$ . In this case, it depends on the value of check residue  $m_{n+1}$ . If, for every different RC modulus condition  $m_i < m_{n+1}$  ( $i = \overline{1, n}$ ) is met, then conclusion can be made that  $d_{\min}^{(RC)} = 2$ , as according to the expression (1), and  $t_{\det.} = 1$ , according to the expression (2). If the condition  $m_i \cdot m_j < m_{n+1}$  ( $i, j = \overline{1, n}; i \neq j$ ) is met across the totality of  $\{m_i\}$  information bases for a random modulus pair, then  $d_{\min}^{(RC)} = 3$  and  $t_{\det.} = 2$ .

Thus, for the NCS in RC given  $k = 1$ , the MCD  $d_{\min}^{(RC)}$  can vary, depending on the value of RC check base  $m_{n+1}$ . Assume, RC is given information bases  $m_1 = 3$ ,  $m_2 = 4$ ,  $m_3 = 5$ ,  $m_4 = 7$  and moreover  $m_k = m_{n+1} = m_5 = 11$ . In this case error verification of any single corrupted NCS residue can be ensured.

Assume, for example,  $m_k = m_{n+1} = 61$ . Ad hoc, we'll draw up a Table 1, mapping information bases to check bases. As Table 1 shows, number representation specificity in RC in some cases allows not only to detect an error, but to find a place of its occurrence with the use of a single check base, which would be impossible to do in the PNS, utilizing existing methods of detecting and correcting errors.

Let's assume, that in the corrupted ( $\tilde{A} \geq M$ ) number  $\tilde{A} = (a_1 \| a_2 \| \dots \| a_{i-1} \| \tilde{a}_i \| a_{i+1} \| \dots \| a_n \| a_{n+1})$  the error  $\tilde{a}_i = (a_i + \Delta a_i) \bmod m_i$  is verified to be present in the residue  $a_i$  modulo  $m_i$ .

Table 1 – Research results of error-correcting capabilities of error control codes in RC ( $l = 1$ )

$m_k = m_{n+1} = m_5 = 61; d_{\min}^{(RC)} = k + 1 = 2, \prod_{i=1}^3 m_i \leq m_5.$				RC information bases	$\prod_{r=1}^k m_{i_r} \leq m_{n+1}$	$k'$	$d_{\min}^{(RC')} = k' + 1$	Max. amount of detectable data errors in RC	Max. amount of correctable data errors in RC
$m_1 = 3$	$m_2 = 4$	$m_3 = 5$	$m_4 = 7$						
+	-	-	-	$3 < 61$	1	2	1	0	
-	+	-	-	$4 < 61$	1	2	1	0	
-	-	+	-	$5 < 61$	1	2	1	0	
-	-	-	+	$7 < 61$	1	2	1	0	
+	+	-	-	$3 \cdot 4 = 12 < 61$	2	3	2	1	
+	-	+	-	$3 \cdot 5 = 15 < 61$	2	3	2	1	
+	-	-	+	$3 \cdot 7 = 21 < 61$	2	3	2	1	
-	+	+	-	$4 \cdot 5 = 20 < 61$	2	3	2	1	
-	+	-	+	$4 \cdot 7 = 28 < 61$	2	3	2	1	
-	-	+	+	$5 \cdot 7 = 35 < 61$	2	3	2	1	
+	+	+	-	$3 \cdot 4 \cdot 5 = 60 < 61$	3	4	3	2	

We'll take a look at the ratio, which makes it possible to correct an error in a given residue  $\tilde{a}_i$  [1].

It's clear that:

$$\tilde{A} = (A + \Delta A) \bmod M_0. \quad (6)$$

Basing on that the error magnitude can be equated to  $\Delta A = (0 \| 0 \| \dots \| 0 \| \Delta a_i \| 0 \| \dots \| 0 \| 0)$ , then the correct ( $A < M$ ) number  $A$  can be expressed as follows:

$$A = (\tilde{A} - \Delta A) \bmod M_0 = [(a_1 \| a_2 \| \dots \| a_{i-1} \| \tilde{a}_i \| a_{i+1} \| \dots \| a_n \| a_{n+1}) - (0 \| 0 \| \dots \| 0 \| \Delta a_i \| 0 \| \dots \| 0 \| 0)] \bmod M_0 = [a_1 \| a_2 \| \dots \| a_{i-1} \| (\tilde{a}_i - \Delta a_i) \bmod m_i \| a_{i+1} \| \dots \| a_n \| a_{n+1}] \bmod M_0.$$

We'll quantify the value of  $A$ . Inasmuch number  $A$  is correct, i.e. is contained in numerical interval  $[0, M)$ , then the following inequality will be fulfilled:

$$A = (\tilde{A} - \Delta A) \bmod M_0 < M. \quad (7)$$

Basing on the value of the error  $\Delta A$  is equal to  $\Delta A = \Delta a_i \cdot B_i$ , then the inequality (7) will be expressed as:

$$\begin{aligned} & \tilde{A} - \Delta a_i \cdot B_i - r \cdot M_0 < M \text{ or} \\ & \tilde{A} - \Delta a_i \cdot B_i - r \cdot M_0 < M_0 / m_{n+1} \quad (r = 1, 2, 3, \dots), \\ & \tilde{A} - (\tilde{a}_i - a_i) \cdot B_i - r \cdot M_0 < M_0 / m_{n+1}, \\ & \tilde{A} - (a_i - \tilde{a}_i) \cdot B_i - r \cdot M_0 < M_0 / m_{n+1}, \\ & (a_i - \tilde{a}_i) \cdot B_i < M_0 / m_{n+1} - \tilde{A} + r \cdot M_0, \\ & a_i - \tilde{a}_i < (M_0 / m_{n+1}) / B_i - \tilde{A} / B_i + r \cdot M_0 / B_i, \\ & a_i < \tilde{a}_i + (M_0 / m_{n+1}) / B_i - \tilde{A} / B_i + r \cdot M_0 / B_i. \end{aligned} \quad (8)$$

Since the orthogonal base of RC module  $m_i$  takes the form of  $B_i = \bar{m}_i \cdot M_0 / m_i$ , then the expression (8) shows up as:

$$\begin{aligned} a_i &< \tilde{a}_i + (m_i + r \cdot m_i \cdot m_{n+1}) / (\bar{m}_i \cdot m_{n+1}) - \tilde{A} / B_i \quad \text{or} \\ a_i &< \tilde{a}_i + m_i (1 + r \cdot m_{n+1}) / (\bar{m}_i \cdot m_{n+1}) - \tilde{A} / B_i. \end{aligned} \quad (9)$$

Inasmuch as the value of the residue  $a_i$  is a natural number, then the value of  $m_i(1 + r \cdot m_{n+1}) / (\bar{m}_i \cdot m_{n+1}) - \tilde{A} / B_i$ , as shown in the expression (9), should be an integer. Thus, taking an integral part of the last ratio, the formula for correcting error in the residue  $\tilde{a}_i$  of the number  $\tilde{A}$  will be:

$$a_i = (\tilde{a}_i + [m_i \cdot (1 + r \cdot m_{n+1}) / (\bar{m}_i \cdot m_{n+1}) - \tilde{A} / B_i] \bmod m_i). \quad (10)$$

We'll have a look at the examples of error correction in RC.

*Example №1.* Perform data verification of the number  $A_{RC} = (0 \| 0 \| 0 \| 0 \| 5)$  and correct it if required, when RC was given information  $m_1 = 3$ ,  $m_2 = 4$ ,  $m_3 = 5$ ,  $m_5 = 7$  and check  $m_k = m_5 = 11$  bases. Thereby,  $M = \prod_{i=1}^n m_i = \prod_{i=1}^4 m_i = 420$  and  $M_0 = M \cdot m_{n+1} = 420 \cdot 11 = 4620$ . Orthogonal RC bases  $B_i$  ( $i = \overline{1, n+1}$ ) are shown in Table 2.

I. Data verification of  $A_{RC} = (0 \| 0 \| 0 \| 0 \| 5)$ . According to the control procedure [1] the value will be defined as:

Table 2 – Orthogonal RC bases  $B_i$  ( $l = 1$ )

$B_1 = (1 \  0 \  0 \  0 \  0) = 1540$ , $\bar{m}_1 = 1$
$B_2 = (0 \  1 \  0 \  0 \  0) = 3465$ , $\bar{m}_2 = 3$
$B_3 = (0 \  0 \  1 \  0 \  0) = 3696$ , $\bar{m}_3 = 4$
$B_4 = (0 \  0 \  0 \  1 \  0) = 2640$ , $\bar{m}_4 = 4$
$B_5 = (0 \  0 \  0 \  0 \  1) = 2520$ , $\bar{m}_5 = 6$

$$\begin{aligned} A_{PNS} &= \left( \sum_{i=1}^{n+1} a_i \cdot B_i \right) \bmod M_0 = \left( \sum_{i=1}^5 a_i \cdot B_i \right) \bmod M_0 = (a_1 \cdot B_1 + a_2 \cdot B_2 + a_3 \cdot B_3 + \\ &a_4 \cdot B_4 + a_5 \cdot B_5) \bmod M_0 = (0 \cdot 1540 + 0 \cdot 3465 + 0 \cdot 3696 + 0 \cdot 2640 + 5 \cdot 2520) \bmod 4620 = \\ &= (5 \cdot 2520) \bmod 4620 = 12600 \bmod 4620 = 3360 > 420. \end{aligned}$$

Thus, in the process of data verification it was evaluated, that  $A_{RC} = 3360 > M = 420$ . In this case, with the possibility of only single errors appearing, conclusion is made that the number in question  $\tilde{A}_{3360} = (0 \| 0 \| 0 \| 0 \| 5)$  is incorrect ( $3360 > M = 420$ ).

In order to correct the number  $\tilde{A}_{3360} = (0 \| 0 \| 0 \| 0 \| 5)$  data is required to be verified first, i.e. corrupted residue  $\tilde{a}_i$  has to be detected. Once done, the true value of the residue  $a_i$  modulo  $m_i$  needs to be defined, whereupon the corrupted residue  $\tilde{a}_i$  should be corrected.

II. Data diagnosing of  $\tilde{A}_{3360} = (0 \| 0 \| 0 \| 0 \| 5)$ . According to the mapping method [1, 2], possible projections  $\tilde{A}_j$  of the number  $\tilde{A}_{3360} = (0 \| 0 \| 0 \| 0 \| 5)$  are:

$$\begin{aligned} \tilde{A}_1 &= (0 \| 0 \| 0 \| 0 \| 5), \quad \tilde{A}_2 = (0 \| 0 \| 0 \| 0 \| 5), \quad \tilde{A}_3 = (0 \| 0 \| 0 \| 0 \| 5), \\ \tilde{A}_4 &= (0 \| 0 \| 0 \| 0 \| 5) \quad \text{and} \quad \tilde{A}_5 = (0 \| 0 \| 0 \| 0 \| 0). \end{aligned}$$

Computational formula for the values  $\tilde{A}_{jPNS}$  of PNS number projections is written as [1]:

$$\tilde{A}_{jPNS} = \left( \sum_{\substack{i=1; \\ j=1, n+1.}}^n a_i \cdot B_{ij} \right) \bmod M_j = (a_1 \cdot B_{1j} + a_2 \cdot B_{2j} + \dots + a_n \cdot B_{nj}) \bmod M_j. \quad (11)$$

According to the expression (11) we'll compute all the values of  $\tilde{A}_{jPNS}$ . Once done, we will make  $(n+1)$  comparison of the  $\tilde{A}_{jPNS}$  numbers to the number  $M = M_0 / m_{n+1}$ . If there are any numbers not being contained in the informational numeric interval  $[0, M)$ , which contains  $k$  correct numbers (i.e.  $\tilde{A}_k \geq M$ ), among  $\tilde{A}_i$  projections, then conclusion is made that these  $k$  residues of the number  $A$  are not corrupted. Only the residues among the rest  $[(n+1) - k]$  number  $\tilde{A}_{RC}$  residues can be false.

The set of the active quotient residues for a given RC and the totality of the quotient  $B_{ij}$  orthogonal bases are shown in Table 3 and Table 4 respectively.

Table 3 – Set of the active quotient RC residues ( $l = 1$ )

$j \backslash i$	$m_1$	$m_2$	$m_3$	$m_4$	$M_j$
1	4	5	7	11	1540
2	3	5	7	11	1155
3	3	4	7	11	924
4	3	4	5	11	660
5	3	4	5	7	420

Table 4 – The totality of the quotient orthogonal RC bases  $B_{ij}$  ( $l = 1$ )

$B_{ij} \backslash i$	$i$	1	2	3	4
$j$					
1		385	616	1100	980
2		385	231	330	210
3		616	693	792	672
4		220	165	396	540
5		280	105	336	120

Now then (Table 4):

$$\begin{aligned} \tilde{A}_{1PNS} &= \left( \sum_{i=1}^4 a_i \cdot B_{i1} \right) \bmod M_1 = (a_1 \cdot B_{11} + a_2 \cdot B_{21} + a_3 \cdot B_{31} + a_4 \cdot B_{41}) \bmod M_1 = \\ &= (0 \cdot 385 + 0 \cdot 616 + 0 \cdot 1100 + 5 \cdot 980) \bmod 1540 = 280 < 420. \end{aligned}$$

Arriving at conclusion, that the residue  $a_1$  of the number  $\tilde{A}_1$  is possibly a corrupted residue  $\bar{a}_1$ ;

$$\begin{aligned} \tilde{A}_{2PNS} &= \left( \sum_{i=1}^4 a_i \cdot B_{i2} \right) \bmod M_2 = (a_1 \cdot B_{12} + a_2 \cdot B_{22} + a_3 \cdot B_{32} + a_4 \cdot B_{42}) \bmod M_2 = \\ &= (0 \cdot 385 + 0 \cdot 231 + 0 \cdot 330 + 5 \cdot 210) \bmod 1155 = 1050 > 420. \end{aligned}$$

Hence, the residue  $a_2$  is ensured being not corrupted;

$$\begin{aligned} \tilde{A}_{3PNS} &= \left( \sum_{i=1}^4 a_i \cdot B_{i3} \right) \bmod M_3 = (a_1 \cdot B_{13} + a_2 \cdot B_{23} + a_3 \cdot B_{33} + a_4 \cdot B_{43}) \bmod M_3 = \\ &= (0 \cdot 616 + 0 \cdot 693 + 0 \cdot 792 + 5 \cdot 672) \bmod 924 = 588 > 420. \end{aligned}$$

Deduced, the residue  $a_3$  is ensured being not corrupted;

$$\begin{aligned}\tilde{A}_{4PNS} &= \left( \sum_{i=1}^4 a_i \cdot B_{i4} \right) \bmod M_4 = (a_1 \cdot B_{14} + a_2 \cdot B_{24} + a_3 \cdot B_{34} + a_4 \cdot B_{44}) \bmod M_4 = \\ &= (0 \cdot 220 + 0 \cdot 165 + 0 \cdot 369 + 5 \cdot 540) \bmod 660 = 60 < 420.\end{aligned}$$

Conclusion: the residue  $a_4$  modulo  $m_4$  of the number  $\tilde{A}_4$  is possibly a corrupted residue  $\bar{a}_4$ ;

$$\tilde{A}_{5PNS} = \left( \sum_{i=1}^4 a_i \cdot B_{i5} \right) \bmod M_5. \text{ Since } M_5 = M = 420,$$

the residue  $\bar{a}_5$  of the check module  $m_k = m_5$  will be always among the totality of possibly corrupted residues  $\bar{a}_i$  of RC number.

Overall conclusion. During data diagnosing of  $\tilde{A} = (0 \parallel 0 \parallel 0 \parallel 0 \parallel 5)$  in NCS, the residues  $a_2 = 0$  and  $a_3 = 0$  were ensured not being corrupted. The residues to the bases  $m_1$ ,  $m_4$  and  $m_5$  might be corrupted, i.e. the residues  $\bar{a}_1 = 0$ ,  $\bar{a}_4 = 0$  and  $\bar{a}_5 = 5$ . In this case it's required to correct the residues  $\bar{a}_1$ ,  $\bar{a}_4$  and  $\bar{a}_5$ .

III. Correcting data errors  $\tilde{A}_{3360} = (0 \parallel 0 \parallel 0 \parallel 0 \parallel 5)$ . According to the acquainted [1] expression:

$$a_i = \left( \bar{a}_i + \left[ \frac{m_i \cdot (1 + r \cdot m_{n+1})}{m_{n+1} \cdot \bar{m}_i} - \frac{\tilde{A}}{B_i} \right] \right) \bmod m_i, \quad (12)$$

we will correct possibly  $\bar{a}_1$ ,  $\bar{a}_4$  and  $\bar{a}_5$  corrupted residues  $a_1$ ,  $a_4$  and  $a_5$ , where  $r = 1, 2, 3, \dots$

It turns out that:

$$\begin{aligned}a_1 &= \left( \bar{a}_1 + \left[ \frac{m_1 \cdot (1 + r \cdot m_{n+1})}{m_{n+1} \cdot \bar{m}_1} - \frac{\tilde{A}}{B_1} \right] \right) \bmod m_1 = \left( 0 + \left[ \frac{3 \cdot (1 + r \cdot 11)}{11 \cdot 1} - \frac{3360}{1540} \right] \right) \bmod 3 = \\ &= (0 + [3, 27 - 2, 18]) \bmod 3 = (0 + [1, 09]) \bmod 3 = (0 + 1) \bmod 3 = 1; \\ a_4 &= \left( \bar{a}_4 + \left[ \frac{m_4 \cdot (1 + r \cdot m_{n+1})}{m_{n+1} \cdot \bar{m}_4} - \frac{\tilde{A}}{B_4} \right] \right) \bmod m_4 = \left( 0 + \left[ \frac{7 \cdot 12}{11 \cdot 4} - \frac{3360}{2640} \right] \right) \bmod 7 = \\ &= (0 + [1, 9 - 1, 27]) \bmod 7 = (0 + [0, 63]) \bmod 7 = (0 + 0) \bmod 7 = 0; \\ a_5 &= \left( \bar{a}_5 + \left[ \frac{m_{n+1} \cdot (1 + r \cdot m_{n+1})}{m_{n+1} \cdot \bar{m}_{n+1}} - \frac{\tilde{A}}{B_5} \right] \right) \bmod m_{n+1} = \left( 5 + \left[ \frac{11 \cdot (1 + 11)}{11 \cdot 6} - \frac{3360}{2520} \right] \right) \bmod 11 = \\ &= (5 + [2 - 1, 3]) \bmod 11 = (5 + [0, 7]) \bmod 11 = (5 + 0) \bmod 5 = 0.\end{aligned}$$

With accordance to the computed residues  $a_1 = 1$ ,  $a_4 = 0$  and  $a_5 = 0$  we are correcting (recovering) the corrupted number  $\tilde{A}_{3360} = (0 \parallel 0 \parallel 0 \parallel 0 \parallel 5)$ , i.e. the corrected number becomes  $\tilde{A}_{cor.} = (1 \parallel 0 \parallel 0 \parallel 0 \parallel 5)$ .

To validate corrected data, as according to the acquainted [1] expression, we'll define the value of the number  $\tilde{A}_{cor.} = (1 \parallel 0 \parallel 0 \parallel 0 \parallel 5)$  in the following way (see Table 2):

$$\begin{aligned}\tilde{A}_{cor.PNS} &= \left( \sum_{i=1}^5 a_i \cdot B_i \right) \bmod M_0 = (a_1 \cdot B_1 + a_2 \cdot B_2 + a_3 \cdot B_3 + a_4 \cdot B_4 + a_5 \cdot B_5) \bmod M_0 = \\ &= (1 \cdot 1540 + 0 \cdot 3465 + 0 \cdot 3696 + 0 \cdot 2640 + 5 \cdot 2520) \bmod 4620 = 14140 \bmod 4620 = 280.\end{aligned}$$

Thus  $280 < M = 420$ , the number  $\tilde{A}_{280} = (1 \parallel 0 \parallel 0 \parallel 0 \parallel 5)$  is correct.

In order to validate correctness of the number  $\tilde{A}_{3360}$  we'll make a computation and comparison of the values to the correct residues  $a_2 = 0$  and  $a_3 = 0$ . In this case they are

$$a_2 = \left( 0 + \left[ \frac{4 \cdot (1 + 11)}{11 \cdot 3} - \frac{3360}{3465} \right] \right) \bmod 4 = 0 \text{ and } a_3 = \left( 0 + \left[ \frac{5 \cdot (1 + 11)}{11 \cdot 4} - \frac{3360}{3696} \right] \right) \bmod 5 = 0. \text{ The result-}$$

ed computations  $a_2 = 0$  and  $a_3 = 0$  of the residues modulo  $m_2$  and  $m_3$  in RC verified correctness of the corrupted number  $\tilde{A}_{3360} = (0 \| 0 \| 0 \| 0 \| 5)$ . Thus, the original number  $\tilde{A}_{RC} = (0 \| 0 \| 0 \| 0 \| 5)$  is corrupted  $\tilde{A}_{3360}$ , wherein the single error  $\Delta a_1 = 1$  occurred modulo  $m_1$ . This error made the correct number  $A_{280}$  being corrupted  $\tilde{A}_{3360}$ .

In order to verify if the correct number  $A_{280}$  is true, subsidiary tests on the process of corruption and correction of the number  $A_{280}$  modulo  $m_1 = 3$  are required. The amount of possible  $N_{CC}$  incorrect (corrupted)  $\tilde{A}_{RC}$  codewords (if only a single error occurred) for each correct  $A_{RC}$  number are

$$N_{CC} = \sum_{i=1}^{n+1} m_i - (n+1).$$

Test results have shown that corruption of the residue  $a_1$  modulo  $m_1 = 3$  of the correct number  $A_{280}$  can produce only two incorrect numbers:  $\tilde{A}_{3360} = (\tilde{0} \| 0 \| 0 \| 0 \| 5)$  and  $\tilde{A}_{1820} = (\tilde{2} \| 0 \| 0 \| 0 \| 5)$ . This points to the fact that the corrected number  $A_{cor.} = A_{280} = (1 \| 0 \| 0 \| 0 \| 5)$  is both correct (is contained in the interval  $[0, 420)$ ) and true. The trueness of the resulted number  $A_{280} = (\hat{1} \| 0 \| 0 \| 0 \| 5)$  is confirmed by the fact that the single error  $\Delta a_1 = 2$  to the base  $m_1 = 3$  converts  $(\tilde{A} = (A + \Delta A) \bmod M_0 =$

$= (1 \| 0 \| 0 \| 0 \| 5) + (2 \| 0 \| 0 \| 0 \| 0) = [(1+2) \bmod 3 \| 0 \| 0 \| 0 \| 5] = (\tilde{0} \| 0 \| 0 \| 0 \| 5)$ ) this number to the unique incorrect number  $\tilde{A}_{3360} = (\tilde{0} \| 0 \| 0 \| 0 \| 5)$ .

*Example №2.* Assume, the correct number is  $A_{280} = (1 \| 0 \| 0 \| 0 \| 5)$  and assume that  $\Delta a_1 = 1$ .

In this case  $\tilde{A} = (A + \Delta A) \bmod M_0 = (1 \| 0 \| 0 \| 0 \| 5) + (1 \| 0 \| 0 \| 0 \| 0) = [(1+1) \bmod 3 \| 0 \| 0 \| 0 \| 5] = (\tilde{2} \| 0 \| 0 \| 0 \| 5)$ . This RC number is relevant to the number 1820 in PNS, i.e. the number  $\tilde{A}_{1820}$  is incorrect. We'll correct the number  $\tilde{A}_{1820}$  now.

Data diagnosing should be made ahead of correcting the number  $\tilde{A}_{1820}$ . To do this we'll map projections  $A_j$  ( $j = \overline{1, 5}$ ) of the number  $\tilde{A}_{1820} = (2 \| 0 \| 0 \| 0 \| 5)$  first. Resulted RC code structures are:  $\tilde{A}_1 = (0 \| 0 \| 0 \| 0 \| 5)$ ,  $\tilde{A}_2 = (2 \| 0 \| 0 \| 0 \| 5)$ ,  $\tilde{A}_3 = (2 \| 0 \| 0 \| 0 \| 5)$ ,  $\tilde{A}_4 = (2 \| 0 \| 0 \| 0 \| 5)$  and  $\tilde{A}_5 = (2 \| 0 \| 0 \| 0 \| 0)$ .

All the projections of  $\tilde{A}_{jPNS}$  are:

$$\tilde{A}_{1PNS} = (5 \cdot 980) \bmod 1540 = 280 < 420 = M;$$

$$\tilde{A}_{2PNS} = (2 \cdot 385 + 5 \cdot 231) \bmod 1155 = 1925 \pmod{1155} = 770 > 420 = M;$$

$$\tilde{A}_{3PNS} = (2 \cdot 616 + 5 \cdot 672) \bmod 924 = 4592 \pmod{924} = 896 > 420 = M;$$

$$\tilde{A}_{4PNS} = (2 \cdot 220 + 5 \cdot 540) \bmod 660 = 3140 \pmod{660} = 500 > 420 = M;$$

$$\tilde{A}_{5PNS} = 2 \cdot 280 \pmod{420} = 560 \pmod{420} = 140 < 420 = M.$$

Inasmuch as  $\tilde{A}_{2PNS}$ ,  $\tilde{A}_{3PNS}$  and  $\tilde{A}_{4PNS} > 420$ , the conclusion is made that the residues  $a_2 = 0$ ,  $a_3 = 0$  and  $a_4 = 0$  of the number  $\tilde{A}_5 = (2 \| 0 \| 0 \| 0 \| 5)$  are not corrupted. Only the residues  $a_1$  and  $a_5$  can be corrupted  $\bar{a}_1 = 2$  and  $\bar{a}_5 = 5$ .

We obtain, that:

$$\begin{aligned} a_1 &= \left( \bar{a}_1 + \left[ \frac{m_1 \cdot (1 + r \cdot m_{n+1})}{m_{n+1} \cdot \bar{m}_1} - \frac{\tilde{A}}{B_1} \right] \right) \bmod m_1 = \left( 2 + \left[ \frac{3 \cdot (1 + 11)}{11 \cdot 1} - \frac{1820}{1540} \right] \right) \bmod 3 = \\ &= (2 + [3, 27 - 1, 18]) \bmod 3 = (2 + [2, 09]) \bmod 3 = (2 + 2) \bmod 3 = 4 \pmod{3} = 1. \end{aligned}$$

Hence, the corrected residue modulo  $m_1$  is  $a_1 = 1$ . In a like manner the residue  $a_5 = 5$ .



Applying the results  $a_1$  and  $a_5$  the corrupted number  $\tilde{A}_{1820} = (\tilde{2} \parallel 0 \parallel 0 \parallel 0 \parallel 5)$  is corrected. As a final result the corrected number is  $A_{280} = (1 \parallel 0 \parallel 0 \parallel 0 \parallel 5)$ .

*Example №3.* Performing verification of the number  $A_{RC} = (0 \parallel 0 \parallel 0 \parallel 2 \parallel 1)$ . In case corruption was detected, data diagnosing and correction should be made.

I. Data checking of  $A_{RC} = (0 \parallel 0 \parallel 0 \parallel 2 \parallel 1)$ . According to the acquainted control procedure  $A_{PNS}$  will be calculated using expression:

$$A_{PNS} = \left( \sum_{i=1}^{n+1} a_i \cdot B_i \right) \bmod M_0 = (0 \cdot 1540 + 0 \cdot 3465 + 0 \cdot 3696 + 2 \cdot 2640 + 1 \cdot 2520) \bmod 4620 = 7800 \bmod 4620 = 3180 > 420. \text{ This number is incorrect } \tilde{A}_{3180}.$$

II. Data diagnosing of  $\tilde{A}_{3180} = (0 \parallel 0 \parallel 0 \parallel 2 \parallel 1)$ . All possible projections  $\tilde{A}_j$  of the number  $\tilde{A}_{3180}$  are:  $\tilde{A}_1 = (0 \parallel 0 \parallel 2 \parallel 1)$ ,  $\tilde{A}_3 = (0 \parallel 0 \parallel 2 \parallel 1)$ ,  $\tilde{A}_4 = (0 \parallel 0 \parallel 0 \parallel 1)$  and  $\tilde{A}_5 = (0 \parallel 0 \parallel 0 \parallel 2)$ .

Calculating the values of all of five projections  $\tilde{A}_j$  in PNS:

$$\begin{aligned} \tilde{A}_{1RC} &= (0 \parallel 0 \parallel 2 \parallel 1) = \tilde{A}_{1PNS} = (a_1 \cdot B_{11} + a_2 \cdot B_{21} + a_3 \cdot B_{31} + a_4 \cdot B_{41}) \bmod M_1 = \\ &= (0 \cdot 385 + 0 \cdot 616 + 2 \cdot 1100 + 1 \cdot 980) \bmod 1540 = 100 < M = 420; \\ \tilde{A}_{2RC} &= (0 \parallel 0 \parallel 2 \parallel 1) = \tilde{A}_{2PNS} = (a_1 \cdot B_{12} + a_2 \cdot B_{22} + a_3 \cdot B_{32} + a_4 \cdot B_{42}) \bmod M_2 = \\ &= (0 \cdot 385 + 0 \cdot 231 + 2 \cdot 330 + 1 \cdot 210) \bmod 1155 = 870 > M = 420; \\ \tilde{A}_{3RC} &= (0 \parallel 0 \parallel 2 \parallel 1) = \tilde{A}_{3PNS} = (a_1 \cdot B_{13} + a_2 \cdot B_{23} + a_3 \cdot B_{33} + a_4 \cdot B_{43}) \bmod M_3 = \\ &= (0 \cdot 616 + 0 \cdot 693 + 2 \cdot 792 + 1 \cdot 672) \bmod 924 = 418 < M = 420; \\ \tilde{A}_{4RC} &= (0 \parallel 0 \parallel 0 \parallel 1) = \tilde{A}_{4PNS} = (a_1 \cdot B_{14} + a_2 \cdot B_{24} + a_3 \cdot B_{34} + a_4 \cdot B_{44}) \bmod M_4 = \\ &= (0 \cdot 220 + 0 \cdot 165 + 2 \cdot 396 + 1 \cdot 540) \bmod 660 = 540 > M = 420; \\ \tilde{A}_{5RC} &= (0 \parallel 0 \parallel 0 \parallel 2) = \tilde{A}_{5PNS} = (a_1 \cdot B_{15} + a_2 \cdot B_{25} + a_3 \cdot B_{35} + a_4 \cdot B_{45}) \bmod M_5 = \\ &= (0 \cdot 280 + 0 \cdot 105 + 2 \cdot 336 + 1 \cdot 120) \bmod 420 = 240 < M = 420. \end{aligned}$$

The calculations of the  $\tilde{A}_{jPNS}$  values and comparing them to the verification interval  $[0, 420)$  range of correct RC numbers  $A_{RC}$  resulted in following. The totality of the residues  $a_2 = 0$  and  $a_4 = 0$  is correct (residues are not being corrupted), while the residues  $\bar{a}_1 = 0$ ,  $\bar{a}_3 = 0$  and  $\bar{a}_5 = 1$  of the incorrect number  $\tilde{A}_{3180} = (0 \parallel 0 \parallel 0 \parallel 2 \parallel 1)$  might be incorrect (could have been corrupted).

III. Correcting possibly corrupted residues  $\bar{a}_1$ ,  $\bar{a}_3$  and  $\bar{a}_5$  of the number  $\tilde{A}_{3180}$ .

Possibly corrupted residues  $\bar{a}_1 = 0$ ,  $\bar{a}_3 = 0$  and  $\bar{a}_5 = 1$  required to be corrected using expression

$$a_i = \left( \tilde{a}_i + \left[ \frac{m_i \cdot (1 + r \cdot m_{n+1})}{m_{n+1} \cdot \bar{m}_i} - \frac{\tilde{A}}{B_i} \right] \right) \bmod m_i. \text{ Then:}$$

$$\begin{aligned} a_1 &= \left( \bar{a}_1 + \left[ \frac{m_1 \cdot (1 + r \cdot m_{n+1})}{m_{n+1} \cdot \bar{m}_1} - \frac{\tilde{A}}{B_1} \right] \right) \bmod m_1 = \left( 0 + \left[ \frac{3 \cdot (1 + r \cdot 11)}{11 \cdot 1} - \frac{3180}{1540} \right] \right) \bmod 3 = \\ &= (0 + [3, 27 - 2, 06]) \bmod 3 = (0 + [1, 21]) \bmod 3 = (0 + 1) \bmod 3 = 1. \end{aligned}$$

Hence,  $a_1 = 1$ .

For the value  $\bar{a}_3$  it is:

$$\begin{aligned} a_3 &= \left( \tilde{a}_3 + \left[ \frac{m_3 \cdot (1 + r \cdot m_{n+1})}{m_{n+1} \cdot \bar{m}_3} - \frac{\tilde{A}}{B_3} \right] \right) \bmod m_3 = \left( 0 + \left[ \frac{5 \cdot (1 + r \cdot 11)}{11 \cdot 4} - \frac{3180}{3696} \right] \right) \bmod 5 = \\ &= (0 + [1, 36 - 0, 86]) \bmod 5 = (0 + [0, 5]) \bmod 5 = (0 + 0) \bmod 5 = 0. \end{aligned}$$

In this case  $a_3 = 0$ .

For the residue  $\bar{a}_5$  value is:

$$a_5 = \left( \tilde{a}_5 + \left[ \frac{m_5 \cdot (1 + r \cdot m_{n+1})}{m_{n+1} \cdot \bar{m}_5} - \frac{\tilde{A}}{B_5} \right] \right) \bmod m_5 = \left( 1 + \left[ \frac{11 \cdot (1 + r \cdot 11)}{11 \cdot 6} - \frac{3180}{2520} \right] \right) \bmod 11 = \\ = (1 + [2 - 1, 26]) \bmod 11 = (1 + [0, 74]) \bmod 11 = (1 + 0) \bmod 11 = 1.$$

Obtaining that  $a_5 = 1$ .

Using the calculated values  $a_1 = 1$ ,  $a_3 = 0$  and  $a_5 = 1$  of the recovered residues the corrupted number  $\tilde{A}_{RC} = (0 \| 0 \| 0 \| 2 \| 1)$  can be corrected, becoming  $A_{RC} = (1 \| 0 \| 0 \| 2 \| 1)$ . Verified by  $100 < 420$ .

### 3 Conclusions of research

Contrary to PNS (positional numeral system), arithmetic RC (residue class) codes feature additional correcting properties. Thus, NCS (non-positional code structure) involves both intrinsic and subsidiary information redundancies, that in some cases results in allowing to correct single errors in RC, while MCD is  $d_{\min}^{(RC)} = 2$ . However, correcting single errors requires performing subsidiary tests of data checking, i.e. time redundancy usage, additionally to information redundancy. Examples of specific implementation of a single error correcting procedures were introduced, that prove reviewed method is possible to be implemented in order to correct data errors in RC.

### References

- [1] Акушский, И. Я. Машинная арифметика в остаточных классах / И. Я. Акушский, Д. И. Юдицкий – М.: Сов. Радио, 1968. – 440 с.
- [2] Krasnobayev, V. A. A method for increasing the reliability of verification of data represented in a residue number system / V. A. Krasnobayev, S. A. Koshman, M. A. Mavrina // Cybernetics and Systems Analysis. – November 2014. – Vol. 50, Issue 6, pp. 969-976.
- [3] Модели и методы обработки данных в системе остаточных классов: [монография] / [Краснобаев В. А., Кошман С., А. и др.] – Харьков: ООО "В деле", 2017. – 197 с.
- [4] Stasev Yu.V., Kuznetsov A.A., Nosik A.M. Formation of pseudorandom sequences with improved autocorrelation properties // Cybernetics and Systems Analysis, Vol. 43, Issue 1, January 2007, pp. 1-11.
- [5] Karpenko O., Kuznetsov A., Sai V., Stasev Yu. Discrete Signals with Multi-Level Correlation Function // Telecommunications and Radio Engineering. – Vol. 71, 2012 Issue 1. pp. 91-98.

**Рецензент:** Сергій Толупа, д.т.н., проф., Київський національний університет імені Т. Шевченка, м. Київ, Україна.  
E-mail: [tolupa@i.ua](mailto:tolupa@i.ua)

Надійшло: Березень 2018.

#### Автори:

Віктор Краснобаєв, д.т.н., проф., заслужений винахідник України, почесний радист СРСР, Харківський національний університет імені В. Н. Каразіна, м. Харків, Україна.

E-mail: [v.a.krasnobaev@gmail.com](mailto:v.a.krasnobaev@gmail.com)

Сергій Кошман, к.т.н., доцент, Харківський національний університет імені В. Н. Каразіна, м. Харків, Україна.

E-mail: [s\\_koshman@ukr.net](mailto:s_koshman@ukr.net)

Максим Силенко, студент, Харківський національний університет імені В. Н. Каразіна, м. Харків, Україна.

E-mail: [maximkasilenko@gmail.com](mailto:maximkasilenko@gmail.com)

Сергій Мороз, к.т.н., Харківський національний технічний університет сільського господарства імені Петра Василенка, м. Харків, Україна.

E-mail: [frost9i@ukr.net](mailto:frost9i@ukr.net)

#### Метод виправлення однократних помилок даних, що представлені кодом класу лишків.

**Анотація.** У даній статті розглянуто метод виправлення одноразових помилок у класі лишків (КЛ). Дослідження даного методу дає можливість створювати ефективні системи контролю помилок даних комп'ютерних систем у КЛ. Результати аналізу коригувальних можливостей арифметичного коду у КЛ показали високу ефективність використання непоозиційних кодових структур, за рахунок наявності у непозиційній кодовій структурі первинної та вторинної надмірності. У роботі показано, що коригувальні можливості кодів у КЛ залежать від введення додаткової надмірності у кодову структуру. При цьому при виконанні певних умов корекція даних може бути проведена введенням тільки однієї контрольної основи. У статті наведені приклади контролю та виправлення одноразових помилок даних, представлених кодами у КЛ.

**Ключові слова:** непозиційна кодова структура; клас лишків; позиційна система числення; мінімальна кодова відстань; завадостійке кодування; діагностика та корекція даних.

**Рецензент:** Сергей Толупа, д.т.н., проф., Киевский национальный университет имени Т. Шевченко, г. Киев, Украина.  
E-mail: [tolupa@i.ua](mailto:tolupa@i.ua)

Поступила: Март 2018.

**Авторы:**

Виктор Краснобаев, д.т.н., проф., заслуженный изобретатель Украины, почетный радист СССР, Харьковский национальный университет имени В. Н. Каразина, г. Харьков, Украина.

E-mail: [v.a.krasnobaev@gmail.com](mailto:v.a.krasnobaev@gmail.com)

Сергей Кошман, к.т.н., доцент, Харьковский национальный университет имени В. Н. Каразина, г. Харьков, Украина.

E-mail: [s\\_koshman@ukr.net](mailto:s_koshman@ukr.net)

Максим Силенко, студент, Харьковский национальный университет имени В. Н. Каразина, г. Харьков, Украина.

E-mail: [maximkasilenko@gmail.com](mailto:maximkasilenko@gmail.com)

Сергей Мороз, к.т.н., Харьковский национальный технический университет сельского хозяйства имени Петра Василенка, г. Харьков, Украина.

E-mail: [frost9i@ukr.net](mailto:frost9i@ukr.net)

**Метод исправления однократных ошибок данных, представленных кодом класса вычетов.**

**Аннотация.** В данной статье рассмотрен метод исправления однократных ошибок в классе вычетов (КВ). Исследование данного метода даёт возможность создавать эффективные системы контроля ошибок данных компьютерных систем в КВ. Результаты анализа корректирующих возможностей арифметического кода в КВ показали высокую эффективность использования непозиционных кодовых структур, за счёт наличия в непозиционной кодовой структуре первичной и вторичной избыточности. В работе показано, что корректирующие возможности кодов в КВ зависят от введения дополнительной избыточности в кодовую структуру. При этом при выполнении определённых условий коррекция данных может быть проведена введением только одного контрольного основания. В статье приведены примеры контроля и исправления однократных ошибок данных, представленных кодами в КВ.

**Ключевые слова:** непозиционная кодовая структура; класс вычетов; позиционная система счисления; минимальное кодовое расстояние; помехоустойчивое кодирование; диагностика и коррекция данных.